

## Technical Data & Instruction Sheet

### PRODUCT BENEFITS

Restores Natural Look of the Stone

Intensifies Natural Color

Protects from Scratches and Scrapes

Fills micro pores

Surface enhancement

### RECOMMENDED SURFACES

Agglomerate Marble, Marble-Cement, Terrazzo, Limestone and other Calcareous Floor.

### AVAILABLE SIZES

1 Ltr & 5 Ltrs

### COVERAGE

100-900 sq. ft. per kg, depending on the texture of the stone

### TECHNICAL INFORMATION

Form: Liquid

Specific Gravity: 1.1

Flash Point: NA

Freeze point: 0°C

pH: < 1

### SHELF LIFE

24 Months

### DESCRIPTION

Crystal+ is water based emulsion of micro-crystal compounds and waxes for final polishing and re-polishing of marble floors. Crystal+ hardens the surface and protects it from scratches and scrapes, giving a durable gloss and restoring the beauty of the material. It is the ideal product for the restoration of worn surfaces by time or by foot traffic.

### DIRECTIONS

Read entire label before using. Use only as directed. Always test on a small area with a 24 hours curing to check desired results. Make sure surface is clean and free of waxes, dirt and coatings. Pro Shine may be applied to damp surfaces only after surface is completely dry. Ensure that that area is well ventilated during the application and the surface is dry. Surface temperature should be between 10°C and 40°C.

1. Ensure area is well ventilated during application and surface is dry. Use respirator. Follow respirator manufacturer's instructions for use.
2. Mask any surface not intended to be treated.
3. Wash the floor thoroughly (we recommend to use our concentrated Cleaner XC1); rinse it well (traces of old wax or grease must be completely removed) and let it dry
4. Apply the product Crystal+ with a sprayer and moisten the surface to be treated (from 1 to 3 m<sup>2</sup>). Immediately pass the single disc polishing machine equipped with steel wool or white pad. **DO NOT ALLOW EXCESS CRYSTAL PLUS TO DRY ON SURFACE.**
5. Slowly keep on working till dry. In this way, Crystallizer Crystal+ while drying on the surface will create the thermo-chemical reaction of crystallization.
6. In case of floor with problems of marked scratches, before crystallization it is recommended a passage with polishing discs or with a smoothing using diamond disks.
7. 15-30 minutes after entire application, wash the entire area with clean water Remove residue, by buffing if left.
8. If Liquid is left to dry, it will cause etch marks on the surface.

### METHOD OF APPLICATION

**DO NOT USE POWER SPRAYER.** Better results will be obtained using a paint brush, pad or roller. For Larger jobs use pump-up garden sprayer. **USE GLOVES, GOGGLES & RESPIRATORS WHILE APPLYING.**

### STORAGE AND HANDLING INSTRUCTIONS

May be harmful if swallowed. May cause skin, eye and respiratory irritation. Do not spray. Avoid prolong exposure to vapors. Use in a well ventilated area. Do not ingest. **KEEP OUT OF THE REACH OF THE CHILDREN.** Do not freeze or store above 40° C. Do not mix with other chemicals.

### EMERGENCY/ FIRST AID PROCEDURES

**Ingestion:** Do not induce vomiting. Call a physician

**Eye Contact:** Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if applicable, and continue flushing. Call a physician if eye irritation persists.

**Skin Contact:** Wash skin with mild soap and water. Call a physician if skin irritation persists. Wash clothes before wearing again.

**Inhalation:** Remove to fresh air. Call a physician if respiratory irritation persists.

*The above information is based on the latest stage of our development and application technology. Due to multiplicity of influencing factors, this information must be considered as non-binding. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any us of this information.*